

REVO Residential Energy Storage Inverters

Split-phase Inverter

Battery voltage > 80V

Product Features:

Safe & Reliable

- Passed UL 1741:2021, IEEE 1547.1, UL1699B test certification; With over-voltage, over-current, over-temperature protection, compatible with anti-zero export function;

Flexible & Efficient

- Supporting critical load priority power supply;
- Support 100% unbalanced load capacity;

Intelligent & Friendly

- Customizable I / O interface, more flexible application;
- Support remote monitoring, remote upgrade and automatic battery management;



Technical Specification:

Technical specification	R6KH1NA	R8KH1NA	R10KH1NA	R12KH1NA
Input (PV)				
Max. power(kW)	7.8	10.4	13	15.6
Max. DC voltage(V)	500			
MPPT voltage range(V)	125 - 500			
Max.Input current of single MPPT(A)	12			
MPPT tracker/strings	4/1			
AC output				
Rated output power(kVA)	6	8	10	12
Max. apparent Power (kVA)	6.6	8.8	11	12
Max. output current(A)	27.5	36.7	45.8	50
Grid voltage/range(V)	240/211~264			
Frequency (Hz)	50/60			
PF	0.8lagging-0.8leading			
THDi	<3%			
AC output topology	Split phase、single phase			
Battery				
Battery voltage range(V)	85~400			
Max. charging voltage(V)	400			
Full battery voltage(V)	85	110	140	160
Max. charge/discharge current(A)	80/80			
Battery type	lithium /Lead-acid			
Communication Interface	CAN,RS485			
EPS output				
Rated power(kVA)	6	8	10	12
Rated output voltage(V)	220-240 /110-120			
Rated frequency(Hz)	50/60			
Automatic switching time(ms)	<20			
THDu	<2%			
Overload capacity	110%,30S/120%,10S/150%,0.02S			
General data				
Max. efficiency	≥98.2%			
CEC efficiency	≥97.2%			
Ingress protection	IP65/NEMA 3R			
Noise emission(dB)	<25	<25	<29	<29
Operation temperature(°C)	-25~60			
Cooling	Natural			
Relative humidity	0 ~95% (non-condensing)			
Operation altitude (m)	2,000 (>2,000 Derating)			
Weight(kg)	34			
Dimensions W * D * H (mm)	560* 220* 680			
Self-consumption(W)	<20			
Display and communication				
Display	LCD			
Interface:RS485/Wifi/4G/ CAN	Yes/ Opt/ Opt/ Yes			
Safety standard	UL1741SA all options, UL1699B, CSA 22.2			
EMC	FCC Part 15, Class B			